

Hi-Output Addressable Sounder

Part No. **QT688/2**



Overview

- A programmable hi-output addressable sounder operating at up to 85dB(A).
- Designed to increase call indication levels in large Quantec sites.
- Can be configured to sound when certain groups of call points are calling.
- Can be assigned one of 16 different tones (four of which are HTM2015 compliant) for each of Quantec's call states using a QT423 configurator.
- Default operation utilises Quantec's standard tones.
- Adjustable day/night volume controls.
- Connections for an optional slave overdoor light.
- Mounts on a standard UK 25mm single gang flush or surface back box.



More Information

Technical Specifications

| | |
|------------------------------------|--|
| Quiescent current | TBC. |
| Nominal SPL (Sound Pressure Level) | Up to 85db(A). |
| Alarm current | TBC. |
| Controls | Adjustable volume controls for day and night mode. |
| Connections | Net +; Net -. Includes R (Red) and G (Green) connections for an optional slave overdoor light. |
| Onboard Sounder | Yes. (Sound sequence changes and intensifies to reflect the urgency of the incoming call as per device programming). |
| Onboard Infrared Receiver | No. |



| | |
|----------------------------------|--|
| Product dimensions (mm) | 86 W x 86 H x 43 D mm. Mounts on a UK 25mm single gang back box. |
| Construction & finish | Plastic. |
| IP Rating | IP41. |
| Weight | 80g |
| Operating conditions/temperature | -5°C to +40°C. Max. relative humidity 95% non-condensing. |
| Notes | Can be programmed using a QT423 configurator. |



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom