

GP001/AB/G2
Heavy Duty Contact



- High Quality Alloy Finish
- Double pole configuration
- Pre-resistored (A,B)
- Other resistor value available
- 57cm Armoured cable lengths
- EN50131-2-6 Grade 2
- Environmental Class II



Specifications

GP001/AB Grade 2

<i>Connections</i>	8 Core x 7/0.2 Copper Cable	<i>Voltage Range</i>	12Vdc
<i>Armoured Cable Length</i>	570mm	<i>Switching Current</i>	500mA @ 12Vdc
<i>Reed Switches</i>	1	<i>Contact Material</i>	Rhodium
<i>Pull-in Gap</i>	45mm	<i>Colours</i>	Brushed Aluminium
<i>Material</i>	Aluminium / ABS	<i>Tamper</i>	Tamper Integrity Loop
<i>Contact Size</i>	85 x 27 x 26mm	<i>Standards</i>	EN50131-2-6 Grade 2
<i>Magnet Size</i>	85 x 27 x 26mm	<i>Environmental Class</i>	II
<i>Contact Form</i>	SPST form A		



Contact us:

Phone:

Tel: +44(0)151 6061000
 Fax: +44(0)151 6061122

Online:

Web: www.cqr.co.uk
 Email: info@cqr.co.uk

Address: CQR Fire & Security, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK.

