



SPEL
Safety in mind



DELTA
PRODUCT DATA SHEET

DELTA



FULLY RECESSED EMERGENCY DOWNLIGHT

FEATURES

- LUMINAIRE DIAMETER OF JUST 50MM.
- EMERGENCY PACKS CAN EASILY PASS THROUGH A CEILING CUT-OUT OF 43-44MM.
- FITTED WITH AN OPEN AREA LENS AS STANDARD BUT IS ALSO SUPPLIED WITH AN ALTERNATIVE CORRIDOR LENS TO ILLUMINATE CENTRE LINES OF ESCAPE ROUTES.
- LED LIFE GREATER THAN 36,000 HOURS.
- LITHIUM LIFEPO4 BATTERY TECHNOLOGY.
- EFFECTIVE OPTICAL DESIGN TO MAXIMISE LIGHT DISTRIBUTION FOR EMERGENCY LIGHTING APPLICATIONS.
- 6500K COLOUR TEMPERATURE.
- PROFICIENT LED DRIVER ALONG WITH ENHANCED THERMAL ENGINEERING TECHNIQUES REDUCE LED OPERATING TEMPERATURES.
- POLYCARBONATE BODY AND DIFFUSER ARE 850°C HOT-WIRE COMPLIANT.
- FOLDABLE DRIVER AND BATTERY PACK FOR EASE OF INSTALLATION IN SHALLOW CEILING VOIDS.
- ALL STATED LUMENS ARE ACTUAL LUMINAIRE OUTPUT.

PRODUCT CODE

CODE	WATTS	EMERGENCY DURATION	OPEN AREA MAINS LUMENS	CORRIDOR MAINS LUMENS	OPEN AREA EMERGENCY LUMENS	CORRIDOR EMERGENCY LUMENS
DEL/LED/NM3	1W	3 HOURS			120	130



EMERGENCY
LUMINAIRE



LED LIGHT
SOURCE



IP20 INGRESS
RATING




3 YEARS
WARRANTY

PRODUCT DATA SHEET




DIMENSIONS

TOP VIEW



SIDE VIEW



DRIVER & EMERGENCY PACK:
LENGTH 250MM X WIDTH 36MM X DEPTH 21MM (DIMENSIONS BASED ON PACK BEING FULLY EXTENDED (PACK IS FOLDABLE FOR EASE OF INSTALLATION))

CUT-OUT:
Ø 43-44MM



SPECIFICATION

GENERAL SPECIFICATION	CONSTRUCTION	CONTROL GEAR	LED'S
<p>CE MARK COMPLIANCE: CE MARKED, REACH, ROHS & UKCA COMPLIANT</p> <p>MANUFACTURED TO STANDARDS: IN ACCORDANCE WITH BS60598-2-22</p> <p>MANUFACTURING QUALITY APPROVAL: ISO 9001:2015</p>	<p>BODY CONSTRUCTION: 85° WHITE POLYCARBONATE BODY / CLEAR POLYCARBONATE LENS</p> <p>PROTECTION DEGREE: IP20</p> <p>INSULATION CLASS: CLASS II</p> <p>CABLING: 90°C SINGLE CORE 0.8MM TO BS6500 GRADE 5</p> <p>SUPPLY VOLTAGE: 220/240V AC 50/60HZ</p>	<p>DESIGN/MANUFACTURE: DESIGNED AND MANUFACTURED IN ACCORDANCE WITH BS EN61347-2-13, BS EN62384, BS EN55015, BS EN61000-3-2 AND BS EN61000-3-3</p> <p>BATTERIES: SUITABLE FOR USE WITH LIFEPO4 3.2V 1500MAH BATTERY TECHNOLOGY</p>	<p>LED TYPE: SINGLE SOURCE 3535</p> <p>LED COLOUR TEMPERATURE: 6500K</p> <p>CRI (MINIMUM): 80</p> <p>LED LIFETIME: TM21 L70 > 36,000 HOURS</p>



SPEL
Safety in mind

HEAD OFFICE

SPEL SAFETY
ORBIK HOUSE
NORTHGATE WAY
ALDRIDGE
WALSALL
WEST MIDLANDS

TEL: 01922 743515
EMAIL: UKSALES@ORBIK.CO.UK



WWW.ORBIK.CO.UK