

## THC-B350-ZM 5 MP VF Bullet Camera



- 5 MP bullet camera
- 2.7 mm to 13.5 mm motorized varifocal lens
- Up to 40 m IR distance for bright night imaging
- Water and dust resistant (IP67)
- One port for four switchable signals (TVI/AHD/CVI/CVBS)

## ▪ Specification

Model		THC-B350-Z
Camera	Image Sensor	5 MP CMOS image sensor
	Max. Resolution	2560 (H) × 1944 (V)
	Min. Illumination	Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
	Shutter Time	PAL: 1/25 s to 1/50, 000 s, NTSC: 1/30 s to 1/50, 000 s
	Day & Night	IR cut filter
	Angle Adjustment	Pan: 0° to 360°; Tilt: 0° to 90°; Rotate: 0° to 360°
Lens	Lens Type	2.7 mm to 13.5 mm motorized vari-focal lens
	Focal Length & FOV	95.7° to 29.1°
	Lens Mount	Φ 14
Image	Image Settings	Brightness, Sharpness, DNR, Mirror, Smart IR
	Frame Rate	PAL: 5 MP@20fps, 4 MP@25fps, 1080p@25fps, NTSC: 5 MP@20fps, 4 MP@30fps, 1080p@30fps
	Day/Night Mode	Auto/Color/BW (Black and White)
	Wide Dynamic Range (WDR)	DWDR
	Image Enhancement	BLC
	White Balance	ATW/MWB
	AGC	Support
Interface	Video Output	Switchable TVI/AHD/CVI/CVBS
General	Material	Metal
	Dimension	253.69 mm × 92.96 mm × 84.09 mm (9.97" × 3.66" × 3.31")
	Weight	Approx. 665 g (1.47 lb.)
	Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
	Communication	Up the coax, Protocol: HIKVISION-C (TVI output)
	Power Supply	12 VDC ±15%, 24 VAC ±15%
	Consumption	DS-2CE16H0T-IT3ZF: Max. 6.3 W ,DS-2CE16H0T-AIT3ZF: Max. 8.9 W
	IR Range	Up to 40 m
Approval	Protection	IP67

## ▪ Available Model

THC-B350-ZM(2.7-13.5mm)(HiLook UK)

## ▪ Dimensions



